

A POMUL 60 DM

A POMUL 60 DM polyvinyl acetate homopolymer, especially designed to be used as carpet back coating adhesive.

TYPICAL PROPERTIES

| | |
|--|------------------------|
| Solid content % | 59.5±1% |
| Chemical basis | Polyvinyl acetate |
| Protective colloid | Polyvinyl alcohol |
| Appearance | Milky emulsion |
| pH | 4-6 |
| Viscosity at 30°C, cps (Brookfield, spindle # 7, 20 rpm) | 20,000 ± 5,000 cps |
| Plasticizer | +ve |
| Film clarity at 25°C | flexible & transparent |
| Water resistance | Good |
| Mechanical stability | Excellent |
| High temperature stability | Good |
| Resistance to air and humidity | Excellent |
| Effect on colors | Non |
| M.F.F.T | 13 |

APPLICATIONS

Apomul 60DM is recommended in particular for carpet back coating, also It is suitable as a binder for nonwoven fabrics.

Apomul 60DM can be used as adhesive to laminate fabrics in clothing and in resin treatment of textile goods.

Apomul 60DM can be diluted easily with water to be applied by spreading, spraying, saturation and foaming.

It can be used at high PVC content, with a good wet abrasion resistance

PACKAGING

Apomul 60DM is available in drums of 125 Kg.

STORAGE

Apomul 60DM is stable for at least 6 months when stored at +5 and 40°.

Please stir well before use.

Keep @ temperature max. 40°C.