

## APOMUL CG 50

APOMUL CG 50 is a polyvinyl acetate emulsion stabilized with poly vinyl alcohol especially designed to be used as adhesives for carton & paper working where high speed machines used, it has high setting time and medium viscosity to be suitable for all kinds of machines.

### TYPICAL PROPERTIES

<b>Solid content %</b>	49 (+) or (-) 1 %
<b>Chemical basis</b>	Polyvinyl acetate
<b>Protective colloid</b>	Polyvinyl alcohol
<b>Appearance</b>	Milky emulsion
<b>pH</b>	3-5
<b>Viscosity at 25 °C</b> (Brookfield Viscometer, spindle # 4 @ 20 rpm)	2,500 – 4,000 cps
<b>Film clarity</b>	clear
<b>Water resistance</b>	Good
<b>Mechanical stability</b>	Excellent
<b>High temperature stability</b>	Good
<b>Resistance to air and humidity</b>	Excellent
<b>PLASTISIZER</b>	+VE

### HANDLING PRECAUTIONS

There is no health risk in handling APOMUL CG 50 the usual precautions in handling chemicals should be observed and it is recommended that operatives should wear goggles and gloves when handling the product.

Any contact with the skin or eyes should be washed immediately with copious amount of cold water.

**Please stir well before use.**

**Keep @ temperature max. 40°C.**