

APOMUL EG PLUS

APOMUL EG plus is a polyvinyl acetate emulsion stabilized with poly vinyl alcohol designed to be used as adhesives for carton & paper and *especially for paper coils*, it's suitable with high speed machines, and characterized by high setting time and medium viscosity to be suitable for all kinds of machines.

TYPICAL PROPERTIES

| | |
|--|-------------------|
| Solid content % | 30 (+) or (-) 1 % |
| Chemical basis | Polyvinyl acetate |
| Protective colloid | Polyvinyl alcohol |
| Appearance | Milky emulsion |
| pH | 3-5 |
| Viscosity at 25 °C (Brookfield Viscometer, spindle # 4 @ 20 rpm) | 2,000 – 4,000 cps |
| Film clarity | clear |
| Water resistance | Good |
| Mechanical stability | Excellent |
| High temperature stability | Good |
| Resistance to air and humidity | Excellent |
| PLASTISIZER | +VE |

HANDLING PRECAUTIONS

There is no health risk in handling **APOMUL EG plus** the usual precautions in handling chemicals should be observed and it is recommended that operatives should wear goggles and gloves when handling the product.

Any contact with the skin or eyes should be washed immediately with copious amount of cold water.

Please stir well before use.

Keep @ temperature max. 40°C.