

## POLIVA CW

**POLIVA CW** is a modified polyvinyl acetate copolymer emulsion, designed to be used for carpet back coating, it is flexible and can accept high amount of fillers and pigments.

### TYPICAL PROPERTIES

<b>Solid content %</b>	50±1%
<b>Chemical basis</b>	Copolymer
<b>Appearance</b>	Milky emulsion
<b>pH</b>	4-5
<b>Viscosity at 30°C</b> (Brookfield Viscometer, spindle # 7@ 20 rpm)	6,000 ± 2,000 cps
<b>Film clarity at 25°C</b>	flexible & transparent
<b>Water resistance</b>	Excellent
<b>Mechanical stability</b>	Excellent
<b>High temperature stability</b>	V. Good
<b>Resistance to air and humidity</b>	Excellent
<b>Effect on colors</b>	Non

### AMOUNT TO BE USED

**POLIVA CW** can be used as is or can be diluted and mixed with fillers.

### HANDLING PRECAUTIONS

There is no health risk in handling **POLIVA CW**. The usual precautions in handling chemicals should be observed and it is recommended that operatives should wear goggles and gloves when handling the product. Any contact with the skin or eyes should be washed immediately with copious amount of cold water.

**Please stir well before use.**

**Keep @ temperature max. 40°C.**