

POLIVA OW-N

POLIVA OW-N is a modified copolymer emulsion, especially designed to be used in high quality manual carpet industries due to its high adhesion power with good finish and flexibility.

TYPICAL PROPERTIES

Solid content % 44 + 2%**Chemical basis** Copolymer Milky emulsion **Appearance**

7-8 Ha

Viscosity at 30°C $11,000 \pm 3,000 \text{ cps}$

(Brookfield Viscometer, spindle # 7@ 20 rpm)

Film clarity at 25°C flexible & transparent

Water resistance Excellent **Mechanical stability** Excellent **High temperature stability** V. Good Resistance to air and humidity Excellent Effect on colors Non

AMOUNT TO BE USED

POLIVA OW-N can be used as is or can be diluted 25%

HANDLING PRECAUTIONS

There is no health risk in handling **POLIVA OW-N** The usual precautions in handling chemicals should be observed and it is recommended that operatives should wear goggles and gloves when handling the product. Any contact with the skin or eyes should be washed immediately with copious amount of cold water.

Please stir well before use.

Keep @ temperature max. 40°C.

Cairo Office: 48 Al Thawra St., Dokki, Giza, Egypt Tel: (+202) 3762 1913 - 3761 6256 Fax: (+202) 3761 5041 Factory: 1st Industrial Zone – Sadat City P.O. Box (34) Tel: (+2048) 260 1011 – 260 0112 Fax: (+2048) 260 1019

E-mail: info@nasydco.com www.nasydco.com