

## POLIVA OW

**POLIVA OW** is a modified copolymer emulsion, especially designed to be used in manual carpet industries cause of its high adhesion power with good finish and flexible carpet.

### TYPICAL PROPERTIES

<b>Solid content %</b>	44±2%
<b>Chemical basis</b>	Copolymer
<b>Appearance</b>	Milky emulsion
<b>pH</b>	7-8
<b>Viscosity at 30°C</b> (Brookfield Viscometer, spindle # 7@ 20 rpm)	10,000 ± 3,000 cps
<b>Film clarity at 25°C</b>	flexible & transparent
<b>Water resistance</b>	Excellent
<b>Mechanical stability</b>	Excellent
<b>High temperature stability</b>	V. Good
<b>Resistance to air and humidity</b>	Excellent
<b>Effect on colors</b>	Non

### AMOUNT TO BE USED

**POLIVA OW** can be used as is or can be diluted 25%

### HANDLING PRECAUTIONS

There is no health risk in handling **POLIVA OW** The usual precautions in handling chemicals should be observed and it is recommended that operatives should wear goggles and gloves when handling the product. Any contact with the skin or eyes should be washed immediately with copious amount of cold water.

**Please stir well before use.**

**Keep @ temperature max. 40°C.**