

## POLIVA CF-V

**Poliva CF-V** is an acetate copolymer emulsion, especially designed to be used for carpet back coating with flexible finish and good binding power.

### TYPICAL PROPERTIES

<b>Solid content %</b>	50 ± 1 %
<b>Protective colloid</b>	anionic/non-ionic
<b>Appearance</b>	Milky emulsion
<b>pH</b>	5 ± 1
<b>Viscosity at 30°C, cps</b> (Brookfield, spindle # 4, 20 rpm)	6,000 ±2,000 cps
<b>Film clarity at 25°C</b>	Flexible & glossy
<b>Water resistance</b>	Excellent
<b>Mechanical stability</b>	Excellent
<b>High temperature stability</b>	Very Good
<b>Resistance to air and humidity</b>	Excellent
<b>Effect on colors</b>	Non
<b>M.F.F.T, °C</b>	5

### APPLICATIONS

**Poliva CF-V** is recommended in particular for carpet back coating, also It is suitable as a binder for nonwoven fabrics with high binding power and flexible finished carpet.

**Poliva CF-V** can be diluted easily with water to be applied by spreading, spraying, saturation and foaming, it doesn't contain any antifoaming agents and compatible to be mixed with other latex like SBR.

### PACKAGING

**Poliva CF-V** is available in drums 125 Kg & IBC 1000Kg.

### STORAGE

**Poliva CF-V** is stable for at least 6 months when stored at +5 and 40°.

**Please stir well before use.**

**Keep @ temperature max. 40°C.**