

POLIVA HT

POLIVA HT is an acetate copolymer, protective free, especially designed to be used for carpet coating applications because it has very small particle size and excellent binding characteristics.

TYPICAL PROPERTIES

Solid content %	48 ± 2 %
Protective colloid	anionic/non-ionic
Appearance	Milky emulsion
pH	5 ± 1
Viscosity at 30°C, cps (Brookfield, spindle # 1, 20 rpm)	≤ 100 cps
Film clarity at 25°C	Clear & glossy
Water resistance	Excellent
Mechanical stability	Excellent
High temperature stability	Very Good
Resistance to air and humidity	Excellent
Effect on colors	Non
M.F.F.T, °C	13

APPLICATIONS

POLIVA HT is recommended in particular for carpet back coating, also it is suitable as a binder for nonwoven fabrics with high binding power and flexible finished carpet.

POLIVA HT can be diluted easily with water to be applied by spreading, spraying, saturation and foaming, it doesn't contain any antifoaming agents and compatible to be mixed with other latex like SBR.

PACKAGING

POLIVA HT is available in drums 125 Kg & IBC 1000Kg.

STORAGE

POLIVA HT is stable for at least 6 months when stored at +5 and 40°.

Please stir well before use.

Keep @ temperature max. 40°C.